



Ozone Pro-Ventor

Advanced Sulfur Removal System

By Smart Ozone Technology



Air Vent Valve with FRP Tank



Venturi Automatic Injector



Ozone Generator

SPECIFICATIONS

- **Oxidation Power:** 300/500 mg/h Ozone Output for rapid disinfection.
- **Energy Efficient:** Ultra-low 13W power consumption.
- **Plug & Play Voltage:** Safe 110V AC operation (American Power Standard).
- **Easy-Installation & Ultra-Lightweight:** 0.5 kg Net Weight for easy mounting.
- **Extended Durability:** Engineered for 10,000 to 15,000 hours of service.

THESE OZONE SYSTEMS PROVIDE:

- **Active oxide ion generation** to achieve high-efficiency, deep sulfur removal for industrial applications.
- **Sulfur Smells:** It instantly destroys the "rotten egg" sulfur smell, leaving your water smelling fresh and clean. **Remove 99.99% Sulfur.**
- **Natural Sterilization:** Ozone is a powerful, natural disinfectant. It kills bacteria and viruses on contact without using any harsh chemicals like bleach or chlorine, **20 times faster than chlorine.**
- **Keep Your Filter Cleaner, Longer:** It prevents slimy "iron bacteria" from growing inside your filter tank. This means your system works better and lasts years longer.
- **Crystal Clear Water:** It doesn't just filter—it polishes. It removes the tea-like tint from well water, making it look as clear as bottled water.

Advanced Sulfur Removal System By Smart Ozone Technology

PRODUCT CHARACTERISTICS

- **Intelligent Auto Start/Stop:** Equipped with a high-sensitivity flow sensor. The system generates ozone water instantly when the tap is turned on and stops automatically when closed—no manual operation required.
- **No Relay Connection Needed.**
- **High-Stability Ozone Output:** Delivers a consistent 300mg/h ozone concentration, ensuring deep sterilization and effective oxidation of dissolved iron and manganese.
- **Food-Grade Safety:** Features a premium 304 stainless steel ozone faucet and food-grade silicone tubing, ensuring the output water remains pure and free from plastic contaminants.
- **Smart Time Display:** An intuitive digital interface displays real-time working duration, allowing you to monitor the system's performance at a glance.
- **Industrial-Grade Durability:** Built with high-quality components designed for a service life of 10,000–15,000 hours.

SIZING CHART: SELECT BEST SYSTEM FOR YOUR APPLICATION

PART #	TANK SIZE (INCH)
PVO3-1054	10 X 54
PVO3-1252	12 X 52
PVO3-1465	14 X 65

Authorized Dealer:

